


## X-RAY DETECTION CIRCUIT IN SEMICONDUCTOR INTEGRATED CIRCUIT DESIGNING

**Patent number:** JP63180884  
**Publication date:** 1988-07-25  
**Inventor:** MORIYA ATSUSHI; others: 01  
**Applicant:** HITACHI MEDICAL CORP  
**Classification:**  
- **international:** G01T1/17; A61B6/03; G01T1/20; H01L31/00  
- **european:**  
**Application number:** JP19870012407 19870123  
**Priority number(s):**

### Abstract of JP63180884

**PURPOSE:** To achieve a higher quality of picture of a CT image with a high accuracy of data obtained, by surrounding a signal input pad into which a signal is inputted from an X-ray detector and a signal wiring pattern to an input terminal of an amplification circuit therefrom with a ground wiring pattern.

**CONSTITUTION:** Conductive parts (a signal input bonding pad 34 and signal wiring pattern 35) to an input terminal of an amplification circuit with a high impedance from a signal input part from an X-ray detector are surrounded with a ground wiring pattern 37 with a low impedance. This portion shields the inflow of an ohmic current and diffusion current to the conductive parts. This eliminates mixture of these currents with signal currents, thereby providing a highly accurate data.



Data supplied from the esp@cenet database - Patent Abstracts of Japan